



ELECTRIC RIM LOCK

CLOUD-BASED ACCESS CONTROL SYSTEM | MOBILE ACCESS

ERL-2DC

FEATURES

- HIGH STRENGTH STAINLESS STEEL LOCK HOUSING
- ELEGANT SURFACE FINISH: STAINLESS STEEL BRUSHED
- SINGLE CYLINDER OR DOUBLE CYLINDER ARE AVAILABLE
- SOLID BRASS BALL LATCH
- SOLID BRASS CYLINDER AND DEADBOLT
- REVERSIBLE DEADBOLT
- FAIL SECURE, PULSE TO OPEN
- RELIABLE LOCKING MECHANISM (UP TO 1000000 OPERATIONS)
- HIGH SECURITY, LOW NOISE

SPECIFICATION & DIMENSION

MODEL ERL-22C

FINISH: NICKLE-PLATED

BACKSET: 60MM
THICKNESS OF LOCK BODY AND STRIKE: 2.0MM
VOLTAGE: 12VDC
WORKING CURRENT: 3A
CONSUMPTION POWER: 10W

UNLOCK TIME: PULSE TO UNLOCK, WITHIN 1S

SERVICE LIFE: 1,000,000 TIMES DIMENSION: 148 X 107 X 60MM

NUVEQ.NET

